

Listing of the Claims:

1. (Amended) A data receiving device for accepting user indicia of authorization on a computer network having a user computer, wherein the user computer includes ~~an input device~~, a display device and a pointer that defines locations on the display device, ~~wherein the input device includes an entry button and is configured to move the pointer in a continuous path on the display device, computer,~~ comprising:

an input device, wherein the input device is configured to control the pointer in the computer and configured to move the pointer in a continuous path on the display device, computer;

a data processor, the data processor further comprising:

a software applet, wherein the software applet configures an input pad comprising a data receiving region, the data receiving region being defined by a matrix grid;

a fitting algorithm, wherein the fitting algorithm is configured to smooth user indicia input into the input pad;

a storage database; and

a processing script, wherein the processing script receives the processed input user indicia and stores the user indicia in the storage database.

2. (Original) A data receiving device as claimed in claim 1, wherein the software applet is configured to receive input data from the input device.

3. (Original) A data receiving device as claimed in claim 2, wherein the input data is a handwritten signature.

4. (Original) A data receiving device as claimed in claim 1, wherein the structure of the matrix grid is defined by pixel coordinates.

Serial No. 09/912,764

5. (Amended) A system for receiving and processing user indicia of authorization, on a computer network, comprising:

a user computer, wherein the user computer includes an input device, a display device and a pointer that defines locations on the display device, wherein the input device ~~includes an entry button and~~ is configured to move the pointer in a continuous path on the display device;

a data processor, the data processor further comprising:

a software applet, wherein the software applet configures an input pad on the display device, comprising a data receiving region, the data receiving region being defined by a matrix grid;

a fitting algorithm, wherein the fitting algorithm is configured to smooth user indicia input in the data receiving region by the user;

a storage database; and

a processing script, wherein the processing script receives the processed ~~input~~ user indicia and stores the indicia in the storage database.

6. (Amended) A system as claimed in claim 4 5 further comprising a data retrieval mechanism.

7. (Amended) A ~~data-receiving device system~~ as claimed in claim 4 5, wherein the software applet is configured to receive input data from the input device.

8. (Amended) A ~~data-receiving device system~~ as claimed in claim 4 7, wherein the input data is a handwritten signature.

9. (Amended) A method for receiving and processing user indicia of authorization on a computer network having a user computer, wherein the user computer includes an input device, a display device and a pointer that defines locations on the display device, wherein the input device

Serial No. 09/912,764

includes an entry ~~button~~ member and is configured to move the pointer in a continuous path on the display device, comprising:

- presenting a user an HTML page containing an applet, wherein the applet configures an input pad having a data receiving region on the display device;
- placing the pointer within the data receiving region via the input device;
- depressing the entry member on the input device;
- moving the pointer within the data receiving region via the input device to create user indicia of authorization within the data receiving region;
- applying a fitting algorithm to the user indicia;
- compressing the user indicia;
- converting the compressed user indicia to a digital bitmap image;
- assigning a unique code to the user indicia; and
- storing the user indicia in a database.

10. (New) A method as claimed in claim 9, further comprising recording field information associated with the user indicia.

11. (New) A method as claimed in claim 9, further comprising retrieving the stored user indicia.

12. (New) A data receiving device as claimed in claim 4, wherein the user indicia is defined by the value of the pixel coordinates upon which the user indicia is deposited in the data receiving region.

13. (New) A data receiving device as claimed in claim 1, wherein the software applet is integrated into an HTML page.

Serial No. 09/912,764

14. (New) A data receiving device as claimed in claim 1, further comprising a data retrieval mechanism, wherein the data retrieval mechanism is configured to restrict access to the storage database

15. (New) A data receiving device as claimed in claim 1, wherein the input device further comprises an entry member, wherein the depression of the entry member activates the data input capability of the input device.

16. (New) A system as claimed in claim 5, further comprising a participant computer, wherein the participant computer is assigned a participant code and a data retrieval mechanism.

17. (New) A system as claimed in claim 16, wherein the data retrieval mechanism is configured to restrict the access of the participant computer to the user indicia stored in the storage database which is associated with the participant code.